



**Relief Valve
RFQ / Order Form**

Date:

Type of Valve Required

- Pressure Vacuum Relief Valve (PVRV)
- Pressure Relief Valve (PRV)
- Vacuum Relief Valve (VRV)
- Other

Type of Venting Required

- Vent to Atmosphere
- Pipe Away

Attach Data Sizing Sheet if available.

Flange Connection Size

- | | |
|-----------|-----------|
| 2" CL 150 | 8" CL 150 |
| 4" CL150 | 10" CL150 |
| 6" CL150 | 12" CL150 |

Seal Material

- PTFE
- Viton
- Buna

Service

- Sweet
- Sour

Body Materials

- | | | |
|--------------|---------------------|-------|
| Aluminum | Stainless Steel 302 | Other |
| Carbon Steel | Stainless Steel 315 | |

Spring Loaded Valves (if applicable)

- Vacuum Setting: 0.4 - 186 oz / 2 mbarg - 0.8 barg
- Pressure Setting: 23.2 oz - 464 oz / 100 mbarg - 2 bar

Weighted Valves (if applicable)

- Vacuum Setting: 0.4 - 23.2 oz / 2 - 100 mbarg
- Pressure Setting: 0.4 - 23.2 oz / 2 - 100 mbarg

PO / Reference #:

Date Required:

Name:

Company:

Phone:

Email:

Shipping Address:

Shipping Options:

Shipping Payment:

Save completed PDF and email to sales@zirco.ca