



JAYCO GASKET SPECIFICATIONS VENT VALVE AND HATCHES

JAYCO VENT VALVES, THIEF HATCHES, AND NON-VENT HATCHES COME STANDARD WITH BUNA N GASKETS DESIGNED TO WORK IN NORMAL (SWEET CRUDE) OPERATIONS OF TANK SYSTEMS IN THE OILFIELD. IF YOUR APPLICATION WILL NOT WORK WITH BUNA N, YOU MUST ORDER THE APPROPRIATE GASKET MATERIAL FOR YOUR SITUATION.

NITRILE**SUPREME65**

SERVICE RATING: -40 TO 220 F

GOOD MECHANICAL & PHYSICAL PROPERTIES,
COMPRESSION SET
UV LIGHT: POOR
A PREMIUM GRADE OF BUNA N.

FLUOROCARBON**VITON FLUOREL**

SERVICE RATING: -45 TO 450 F

RESIST TO: ACIDS (EXCELLENT), FUELS AND OIL (EXCELLENT), AROMATIC
HYDROCARBONS (EXCELLENT), CHLORINATED SOLVENTS (EXCELLENT),
ALCOHOLS (EXCELLENT)
UV LIGHT (EXCELLENT)
WEATHERING AND OZONE (EXCELLENT).
RECOMMENDED FOR H2S PRODUCTION.

9412 NICHOLS ROAD • PO BOX 20026 • OKLAHOMA CITY, OK 73156

800-654-9263 • 405-751-6903 • FAX 405-755-7940 • WWW.JAYCO.ORG