



JAYCO SUPER SEAL

INTRODUCING THE IMPROVED JAYCO VENT VALVE FEATURING JAYCO SUPER SEAL TECHNOLOGY. THESE VALVES INCOPORATE AN O-RING PRESSURE VACUUM PLUNGER THAT UPDATES THE SEALING PERFORMANCE TO WHAT CUSTOMERS HAVE COME TO EXPECT FROM JAYCO JT-8.1 THIEF HATCHES.

THE NEXT GENERATION OF JAYCO VENT VALVE

- GREATER SEALING PERFORMANCE
- EXCEEDS API2000 STANDARDS FOR ALLOWABLE LEAKAGE
- LESS THAN 0.5 SCFH @ 90% SET PRESSURE
- IMPROVED PRESSURE FLOW RATES
- COMES STANDARD WITH VACUUM RELIEF
- AVAILABLE IN 2, 3, AND 4 INCH VALVES
- INLINE PIPE AWAY & STACK VENT TO ATMOSPHERE
- DIAL IN THE PRESSURE SETTING WITH 1/2 OZ INCREMENTS
- O-RING COMES STANDARD IN VITON®
- OPTIONAL VACUUM GASKET IN VITON®

ORIGINAL JAYCO VENT VALVES CAN BE RETROFITTED WITH THE JAYCO SUPER SEAL PLUNGERS IN FOUR EASY STEPS. VISIT THE VENT VALVE PAGE AT WWW.JAYCO.ORG TO FIND OUT MORE ON THE PREVIOUS MODEL.



VITON® IS A REGISTERED TRADEMARK OF DUPONT DOW ELASTOMERS

9412 NICHOLS ROAD • PO BOX 20026 • OKLAHOMA CITY, OK 73156

800-654-9263 • 405-751-6903 • FAX 405-755-7940 • WWW.JAYCO.ORG