

Relief Valve RFQ / Order Form

Date:

Type of Valve Required

Pressure Vacuum Relief Valve (PVRV)

Pressure Relief Valve (PRV)

Vacuum Relief Valve (VRV)

Other

Type of Venting Required

Vent to Atmosphere

Pipe Away

Attach Data Sizing Sheet if available.

Flange Connection Size

2" CL 150

8" CL 150

4" CL150

10" CL150

6" CL150

12" CL150

Seal Material

PTFE

Viton

Buna

Service

Sweet

Sour

Body Materials

Aluminum

Stainless Steel 302

Other

Carbon Steel

Stainless Steel 315

Spring Loaded Valves (if applicable)

Vacuum Setting: 0.4 - 186 oz / 2 mbarg - 0.8 barg

Pressure Setting: 23.2 oz - 464 oz / 100 mbarg - 2 bar

Weighted Valves (if applicable)

Vacuum Setting: 0.4 - 23.2 oz / 2 - 100 mbarg

Pressure Setting: 0.4 - 23.2 oz / 2 - 100 mbarg

PO / Reference #:

Date Required:

Name:

Company:

Phone:

Email:

Shipping Address:

Shipping Options:

Shipping Payment:

Save completed PDF and email to sales@zirco.ca